Dye procedure options

- 1. One colour Use on figured grain for highlights or colour change for regular grain
- Two colours, no sanding of first colour Use on regular or figured grain. Yields a third colour (i.e. blue + yellow = green) or highlight areas of flat and end grain with shades of tertiary colour (usually on turnings more than flat work because turnings have flat and end grain unless turned end grain).
- *3.* **Two colours, sanding back the first** *Use on figured grain. Yields tertiary colour with blends between darker and lighter shades.*
- 4. Black plus one colour, sanding back the black Use on figured grain. Yields black or very dark colour highlights plus second colour.
- 5. Black plus two colours, sanding back black and first colour Use on figured grain. Yields black or very dark tertiary highlights with blends of darker and lighter tertiary colours.
- 6. Three colours Use on figured grain or regular grain. Darker colour first, mid second and lightest last. Use sanding techniques for black/two colour. Yields tertiary colour of dark and combination of last two primaries (i.e., blue + red + yellow = shades of brown in figured wood, [same as blue + orange= brown]). When used on regular grain, yields one tertiary colour.
- 7. Note when applying black and first colour wipe down with damp cloth after application to remove excess dye. Saves a lot of sanding.
- 8. Note that primary colours (Blue, Red, Yellow) are the only colours required.
- 9. Use a colour wheel (art stores) if not familiar with combining colours
- **10. Sanding procedures.**
 - **Two colour:** Sand back first colour to various degrees (aggressive or light) depending on desired effect. Use 150 or 180 then 220
 - Black and one colour: Sand the black aggressively (150/180/220 or even 120/180/220) then apply second colour. No need to sand tertiary colour but can for lighter highlights.
 - Black and two colours: Sand the black aggressively (150/180/220 or even 120/180/220) then sand first colour back (180/220). No need to sand second colour but can for lighter highlights.
 - Do all sanding by hand with a view to highlighting areas of interest.
 - Sanding after application of finish will bring out lighter highlights so attention must be paid to that.